



CS 3050ci | Color Multifunctional System

Powering Color  
Performance...  
Company-wide.



# CS 3050ci



Shown with optional 175 sheet DSDP and 500 x 2 sheet paper trays



Shown with optional 175 sheet DSDP, 1,500 x 2 sheet paper trays and 1,000 sheet finisher



Shown with optional 175 sheet DSDP, 500 x 2 sheet paper trays and 4,000 sheet finisher



Newly designed, easy-to-use large color touch screen control panel

**HyPAS™**

Hybrid Platform for Advanced Solutions



## Basic Specifications

|                          |                                                                                                                         |
|--------------------------|-------------------------------------------------------------------------------------------------------------------------|
| Configuration            | Color Multifunctional System – Print/Scan/Copy/Optional Fax                                                             |
| Pages Per Minute         | Color and Black - Letter: 30 ppm, Legal: 18 ppm, Ledger: 15 ppm, 12" x 18": 15 ppm (print only)                         |
| Warm-up Time             | 25 Seconds or Less (Power On)                                                                                           |
| First Page Out           | Copy: 6.2 Seconds or Less Black, 8.1 Seconds or Less Color; Print: 7.3 Seconds or Less Black, 9.5 Seconds or Less Color |
| Resolutions / Bit Depth  | 600 x 600 dpi; 9600 x 600 dpi interpolated / 8 bit depth                                                                |
| Memory / Hard Disk Drive | 2 GB RAM Standard / 160 GB HDD                                                                                          |
| Duplex                   | Standard Stackless Duplex Supports Statement to 12" x 18", 16 lb Bond - 120 lb Index (60 – 220gsm)                      |
| Standard Output Tray     | Statement - 12" x 18" / 250 sheets; up to 12" x 47" Banner/Single Sheet                                                 |
| Electrical Requirements  | 120V, 60Hz, 12.0A                                                                                                       |
| Dimensions / Weight      | 26.30" W x 30.20" D x 29.41" H / 251.33 lbs                                                                             |
| Max Monthly Duty Cycle   | 150,000 Pages Per Month                                                                                                 |

## Paper Supply

|                        |                                                                                                                                                                                           |
|------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Standard Paper Sources | Dual 500 Sheet Trays, 150 Sheet MPT; Auto Selection/Switching                                                                                                                             |
| Optional Paper Sources | Dual 500 Sheet Trays ( <b>PF-730</b> ), Dual 1,500 Sheet Trays ( <b>PF-740</b> ); 3,000 Sheet Large Capacity Tray ( <b>PF-770</b> )                                                       |
| Paper Capacity         | Standard: 1,150 Sheets; Maximum: 7,150 Sheets                                                                                                                                             |
| Paper Size             | Trays 1, 2 and <b>PF-730</b> : 5.5" x 8.5" – 12" x 18"; <b>PF-740</b> , <b>PF-770</b> : 8.5" x 11"; MPT: 5.5" x 8.5" – 12" x 18" (Multiple Sheets); Up to 12" x 47" Banner (Single Sheet) |
| Paper Weight           | Trays: 16 lb Bond – 120 lb index (60 – 220gsm); MPT: 16 lb Bond – 110 lb Cover (60 – 300gsm)                                                                                              |
| Input Materials        | Bond Paper, Recycled Paper, Transparencies, Cardstock, Envelopes                                                                                                                          |

## Print Specifications

|                                       |                                                                                                                                             |
|---------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------|
| Standard Controller                   | IBM PowerPC 750CL / 600 MHz                                                                                                                 |
| PDLs / Emulations                     | PRESCRIBE, PCL6 (5c, XL), KPDL3 (PS3), XPS; Optional: UG-34 IBM ProPrinter, Diablo 630, LQ-850                                              |
| Fonts                                 | 136 KPDL3, 93 PCL6, 8 Windows Vista, 1 Bitmap                                                                                               |
| Windows OS Compatibility              | Windows XP/2003/Vista/2008/7                                                                                                                |
| Novell OS Compatibility               | Novell NetWare 3.x/4.x/5.x/6.x                                                                                                              |
| MAC OS Compatibility                  | Mac OS 10.x                                                                                                                                 |
| UNIX OS Compatibility                 | Sun OS 4.1.x; Solaris 2.x; AIX; HP-UX (LPR)                                                                                                 |
| Interfaces                            | Standard: 10/100/1000BaseTX, Hi-Speed USB 2.0, 2 USB Host Interfaces, 2 Expansion Slots<br>Optional: 10/100/1000BaseTX (IB-50 for Dual NIC) |
| Network Print and Supported Protocols | TCP/IP, IPX/SPX, AppleTalk, NetBEUI, IPv6, IPsec, SSL, WSD Print                                                                            |
| Drivers                               | KX Driver, Mini Driver, KX Driver for XPS, XPS Mini Driver, Network Fax Driver, PPD for MAC                                                 |
| Utilities                             | PRESCRIBE, PDF Direct Print, KMnet Admin, KMnet Viewer, Kyocera Command Center RX                                                           |

## Scan Specifications

|                                    |                                                                                                                                                                                                                 |
|------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Scan Resolution                    | 200, 300, 400, 600 dpi                                                                                                                                                                                          |
| File Formats                       | BW: TIFF, XPS, PDF, PDF/A; Color: TIFF, JPEG, XPS, PDF, PDF/A                                                                                                                                                   |
| PDF Extension                      | High Compression PDF, Encrypted PDF                                                                                                                                                                             |
| Scan Speeds                        | <b>DP-770</b> : Simplex: 65 ipm BW, 65 ipm Color (300 dpi); Duplex: 39 ipm BW, 39 ipm Color (300 dpi)<br><b>DP-771</b> : Simplex: 70 ipm BW, 70 ipm Color (300 dpi); Duplex: 100 ipm BW, 80 ipm Color (300 dpi) |
| Connectivity / Supported Protocols | 10/100/1000BaseTX, TCP/IP                                                                                                                                                                                       |
| Scanning Functions                 | Scan to Folder (SMB), Scan to e-Mail, Scan to FTP, Scan to USB, WSD Scan, TWAIN Scan                                                                                                                            |
| Original Size                      | Through DP: Statement to 11" x 17"; Glass: up to 11" x 17"                                                                                                                                                      |
| Driver                             | TWAIN/WIA Driver                                                                                                                                                                                                |

## Copy Specifications

|                                       |                                                                                                                                                                                 |
|---------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Image Mode                            | Text, Photo, Text/Photo, Auto, Manual, Map                                                                                                                                      |
| Continuous Copy                       | 1 – 999 / Auto Reset to 1                                                                                                                                                       |
| Additional Features                   | Positive/Negative Reverse, Mirror Image, Rotate Copy, Border Erase, Split Copy, Electronic Sort, Margin Shift, Page Number, Form Overlay, XY Zoom, Prevent Bleed Through, Stamp |
| Job Management                        | 1,000 Department Codes, Job Programs, Job Build, Shortcut Keys, Repeat Copy                                                                                                     |
| Color Adjustment                      | One Touch, Hue, Auto Exposure, Sharpness                                                                                                                                        |
| Magnification / Zoom                  | Full Size, 5 Reduction, 5 Enlargement Preset Ratios, 25 – 400% in 1 step increments                                                                                             |
| Document Box                          | Custom Box, Job Box, Removable Memory Box, Fax Box (with optional Fax System)                                                                                                   |
| Document Processor                    | Optional DP-770 or DP-771                                                                                                                                                       |
| Type / Capacity                       | <b>DP-770</b> : Reversing Automatic Document Processor / 100 Sheets<br><b>DP-771</b> : Dual Scan Document Processor / 175 Sheets                                                |
| Acceptable Originals                  | 5.5" x 8.5" – 11" x 17"                                                                                                                                                         |
| Acceptable Weights (Simplex / Duplex) | ( <b>DP-770</b> ) Simplex: 13 lb Bond – 90 lb Index; Duplex 16 – 32 lb Bond<br>( <b>DP-771</b> ) Simplex: 13 lb Bond – 120 lb Index; Duplex: 16 lb Bond – 120 lb Index          |

## Fax Specifications

|                                  |                                                                                 |
|----------------------------------|---------------------------------------------------------------------------------|
| Compatibility / Data Compression | G3 Fax / MMR, MR, MH, JBIG                                                      |
| Transmission Speed / Modem Speed | Approximately 3 seconds per page / 33.6 Kbps                                    |
| Fax Memory                       | Standard: 12 MB; Maximum: 120 MB                                                |
| Driver                           | KM Network Fax Driver                                                           |
| Fax Functions                    | Duplex TX/RX, Confidential RX/TX, F-Code RX/TX, Broadcasting, Fax Box, Dual Fax |

## Optional 1,000 Sheet Finisher

|                         |                                                                                                                |
|-------------------------|----------------------------------------------------------------------------------------------------------------|
| Stack / Staple Capacity | Main Tray: 1,000 Sheets / 50 sheets (up to 24 lb Bond (90gsm))                                                 |
| Paper Size              | 5.5" x 8.5" – 12" x 18"                                                                                        |
| Paper Weight            | 16 lb Bond – 110 lb Cover (60 – 300gsm)                                                                        |
| Edge Staple Position    | 3 Positions: Top Left, Bottom Left, Center Bind                                                                |
| Optional Punch          | <b>PH-7A</b> 2 and 3 Hole Punch Unit, Supports 8.5" x 11" – 11" x 17"; 13 lb Bond – 110 lb Cover (45 – 300gsm) |

## Optional 4,000 Sheet Finisher

|                                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|-----------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Stack / Staple Capacity                 | Main Tray: 4,000 Sheets; Sub Tray (B): 200 Sheets; Sub Tray (C): 100 Sheets / 65 sheets (up to 24 lb Bond (90gsm))                                                                                                                                                                                                                                                                                                                                               |
| Paper Size                              | 5.5" x 8.5" – 12" x 18"                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Paper Weight                            | 16 lb Bond – 110 lb Cover (60 – 300gsm)                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Edge Staple Position                    | 3 Positions: Top Left, Bottom Left, Center Bind                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Optional Multi-bin Mailbox              | <b>MT-730</b> Includes 7 Trays; Supports 16 lb Bond – 90 lb Index (60 – 163gsm)<br>Stack Capacity per bin: 100 Sheets: 5.5" x 8.5", 8.5" x 11"; 50 Sheets: 8.5" x 14", 11" x 17"                                                                                                                                                                                                                                                                                 |
| Optional Punch                          | <b>PH-7A</b> 2 and 3 Hole Punch Unit, Supports 8.5" x 11" – 12" x 18"; 13 lb Bond – 110 lb Cover (45 – 300gsm)                                                                                                                                                                                                                                                                                                                                                   |
| Optional Booklet Folder / Tri-fold Unit | <b>BF-730</b> Booklet Folder Supports 8.5" x 11", 8.5" x 14", 11" x 17"; 16 lb Bond – 24 lb Bond (60 – 90gsm)<br>16 sheets; 25 lb Bond – 28 lb Bond (91 – 105gsm) 13 sheets; Fold booklet – no staple: 16 lb Bond – 24 lb Bond (60 – 90gsm) 5 sheets; 25 lb Bond – 72 lb Index (91 – 120gsm) 3 sheets; 32 lb Bond – 110 lb Cover (121 – 256gsm) 1 sheet; Trifold: 16 lb Bond – 24 lb Bond (60 – 90gsm) 5 sheets; 25 lb Bond – 72 lb Index (91 – 120gsm) 3 sheets |

## Additional Options

|  |                                                                                                                                                                                                        |
|--|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  | Data Security Kit Provides Security Overwrite and Encryption for Print, Copy, and Scan, Optional System Memory, Optional Fax Memory, Original Hardcopy Holder (Document Tray), Card Authentication Kit |
|--|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

Specifications and design are subject to change without notice.

For the latest on connectivity visit [www.copystar.com](http://www.copystar.com)

All trademarks are the property of their respective owners.

Kyocera Mita America, Inc. Headquarters: 225 Sand Road, Fairfield, NJ 07004-0008, USA

©2011 Kyocera Mita America, Inc.

IC# 855D400291

